

## HOW TO APPLY

### TECHNICAL INFORMATION

**COVERAGE** 13-15 m<sup>2</sup> / liter / coat

**APPLICATION** Brush / Roller / Spray Gun

**THINNER** Clean Water

**DRYING TIME** 2-3 hours between coats

**NO OF COATS** 3-4

**THINNING** By Roller / Brush 50-75%  
By Spray 25%

**CLEANING** Clean all equipment with water

### SURFACE PREPARATION

Surfaces must be clean, dry and free from all surface contamination. Treat mould with bleach then rinse with fresh water. After priming with Wallman Primer, fill and smooth the surface with Wallman Wall Putty.

### REPAINT

Remove all loose and flaking paint. Spot bare areas with Wallmanprimer.)

### STIRRING

Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency.

### AFTER PAINTING

Avoid exposure to steam for 48 hours. Surface may be washed after 7 days, but always avoid abrasive cleaners.

### CLEAN UP

Water: Scrape excess paint from equipment into a separate container. Wash up with water. Do not dispose of paint or wash water into drains or sewers.



Extreme Durability



Flexible Paint Film



Long Lasting Protection



High Scrub Resistance



UV Resistant



Quick Drying



Breathable



Resist Hairline Cracking



Water Based  
Low Odour



Stain Resistant



Antimicrobial



High Color Retention

### TYPICAL SURFACES

- New surfaces.
- Previously painted surfaces.
- Powdery dusty surfaces. (With cracks and other surface defects)

### FINISH



FLAT

LOW SHEEN

HIGH SHEEN

SEMI GLOSS



SMOOTH